



Bonded Seals French metric

Thread Diameter M	Size reference	OD +0.13 -0.00	Id +0.13	Thickness	Minimum burst pressure bar
3	301	7.50	3.60		1980
4	302	9.00	4.60	1.00	2000
5	303	10.00	5.60		1780
6	304	11.00	6.60		1680
6	305	13.27	6.85	1.30	1970
6	306	11.40	7.00	1.00	1540
8	307	13.00	8.60		1330
10	310	17.00	10.70		1730
11	311	18.10	11.80		1610
12	312	19.00	12.70	1.50	1530
13	315	20.10	13.80		1430
14	316	21.00	14.70		1370
16	317	23.00	16.70		1240
16.5	319	23.90	17.20	2.10	1020
17	318	23.70	17.40	1.50	1130
18	320	27.00	18.70		1450
20	321	29.00	20.70		1340
21	323	30.00	21.70		1290
22	324	31.00	22.70		1240
23	325	32.00	23.70		965
24	326	33.00	24.70	2.00	1160
26	327	35.30	27.00		860
27	328	36.00	27.70		1060
28	329	36.00	28.60		7220
28.5	330	37.50	29.20		810
30	331	39.00	30.70		970
33	332	42.00	33.70		900
36	333	48.00	37.00		1010
39	334	51.00	40.00		950
42	335	54.00	43.00	2.50	890
45	336	57.00	46.00		860
48	337	60.00	49.00		790